



### JOLLYVILLE TRANSMISSION MAIN: Environmental Commissioning Monthly Report

Presented to the Austin Environmental Board October 17, 2012

Thais Perkins, Watershed Protection Department David Johns, Watershed Protection Department







### **Environmental Commissioning Activities - JVTM**

- Monthly shaft site (surface) visits concurrent with plant site visits
- Biweekly shaft/tunnel visits to active shafts (4Points, Jollyville) and tunnel reaches (R2, R3)
- Biweekly meetings of the Environmental Commissioning Coordination Group (ECCG) to resolve possible issues
- Environmental Monitoring
  - Increased monitoring schedule at adjacent sites as mining progresses in Reach 2, Reach 3 and Spicewood Shaft
  - Age Dating sampling 90-95% complete (still will take samples in tunnel once it progresses)
  - Dye Trace Results




# **Environmental Commissioning Cost Summary**


Total Remaining	\$ 403,225
Total Amount Billed to Date (work from July 2012)	\$ 1,310,589
Initial INTERA Contract Amount	\$ 1,713,814




### Groundwater Monitoring Well Summary

- West side wells (along tunnel route, Ed/Walnut contact): steady
- Piezometer wells in the BCP along tunnel route: steady
- Spicewood shaft wells reflect rainfall; no shaft influence evident
- East side wells in the Glen Rose continue to decline; shallower Ed/Walnut wells steady.







City of Austin DRAFT: QA/QC review pending




#### Hydrographs for Western Area, Deep




### Spicewood Shaft Wells






#### **East Side Wells**




 JT-126 and JT-125 continue to decline. JT-104 shows similar recent trend.





#### Environmental Monitoring Update – Surface flow



Trib 4 by Spicewood Shaft 7/25/12

- All springs and stream reaches flowing
- Water quality parameters within expected ranges
- Nondetects for indicators of mining, vehicular operation, and drilling (TPH, Cu, Cr, Zn)
- Nondetects for di-n-butyl grout compounds in JT-112, Gaas spring



### Jollyville Plateau Salamander Monitoring

Site	Date of Last Count	Count #	Historical Average (& last four counts)
Lanier	Sept 7, 2012	100	65 (100,56,48,59)
Franklin/Pit	May 18, 2012	100	78 (73,87,39,100)
Tanglewood	May 16, 2012	3	8 (0,0,0,3)
Lower Ribelin	September 2012	94	94 (176,43,42,94)
Upper Ribelin	May 23, 2011	75	64 (123,74,67, 75)
Trib 4 @ Spicewood	August 1, 2012	0	10 (20, 9, 2,0)


-- provided by Nathan Bendik, Salamander Biologist for WPD




## JVTM Environmental Monitoring Summary (cont.)

Trigger	Range	Recent Occurrences
TROLL Alarms	Outside of range of historical Variability	None
Tunnel Inflow Triggers	Baseline water inflow triggers: 50 gpm over 10 feet of tunnel length 200 gpm over 500 feet of tunnel length 400 gpm over a single tunnel reach (1, 2, or 3)	No measurable water inflows
	Sensitive area triggers: 25 gpm over 10 ft of tunnel length 100 gpm over 500 ft of tunnel length	No tunneling in sensitive areas
Spring/Streamflow Triggers	Relative to one another; paired comparison analysis	All surface sites responding consistently with rainfall and general trends









Thais Perkins, Environmental Commissioning Coordinator
David Johns, Hydrogeologist
Watershed Protection Department
<a href="mailto:thais.perkins@austintexas.gov">thais.perkins@austintexas.gov</a>
974-2291