## RIGHT OF WAY MANAGEMENT STANDARD NOTES FOR TRAFFIC CONTROL PLANS

- 1. Contractor shall have an approved right of way (ROW) permit and traffic control plan (TCP) in electronic or paper formats on site at all times when working in the ROW.
- 2. Contractor shall provide notification, as per the latest Mobility Guidelines (MG-04).
- 3. Unless otherwise approved by the ROW Division of Austin Transportation Department (ATD): a.) Only one phase of a TCP may be set at any one time, and b.) Initial setup and phase changes of long-term work zones shall be installed on weekends.
- 4. Once traffic control has been set, the authorized and competent representative from the project team/barricade company will complete and upload the "Contractor's Self-Inspection Checklist" form. See form and detailed instructions here: https://www.austintexas.gov/page/right-way-traffic-control
- 5. For ROW violations, an investigation fee will be assessed for each offense until the violation is corrected. See current fee schedule here: https://www.austintexas.gov/sites/default/files/files/Transportation/Right\_of\_Way/Approved\_ROW\_Fees.pdf
- 6. Excavations shall be backfilled or plated when required to open to traffic. Temporary paving shall be done according to City of Austin (COA) Standard Detail 1100S-4 (for HMAC or PCC pavements). For excavations exceeding a transverse width of 5 feet, the contractor shall provide an engineered plating plan for review by the City.
- 7. Pedestrian routes in and around the work zone, including construction entrances, temporary walking paths, bypasses, covered walkways, and detours, must remain accessible and ADA compliant throughout the project.
- 8. All applicable safeguards shall be in place per Chapter 33 of the International Building Code, to include pedestrian protections per Section 3306.
- "Construction Entrance Ahead" signs must be placed at all approaches to construction entrances, unless otherwise shown on the approved TCP.
- Existing driveways shall not be closed except with advance notice to the affected businesses/residences and approval from the ROW Division of ATD.
- 11. All traffic control devices including protective barriers must be crashworthy and installed according to the manufacturer's guidelines. Crashworthiness shall be determined per MASH testing requirements.
- 12. Overnight protection of work zones and storage of material/equipment shall be according to COA Standard Detail 804S-4.
- 13. The name of the barricade contractor shall be shown on the non-reflective surface of all traffic control devices in accordance with COA Standard Detail 804S-5.
- 14. The City's traffic engineer or inspector may make or require field adjustments to address issues of safety and mobility.
- 15. If existing Capital Metro bus stops are within the temporary traffic control or detour area, the contractor shall contact Capital Metro (Laurie Michel at 512-621-5713 (Mobile)/ 512-369-7701 (Work), Laurie.Michel@capmetro.org), or ~service.impacts@capmetro.org, two (2) weeks prior to setting up the traffic control devices in order to coordinate potential bus-stop relocation or any other related issues.
- 16. If existing signalized intersections are within the temporary traffic control area, the contractor shall contact ATD Signals Division at (512) 974-4075, one week prior to setting traffic control devices.
- 17. The right of way shall be returned to full use at the end of the approved work hours.
- 18. Contractors shall adhere to all ROW special event activity restrictions, as per the latest Mobility Guidelines (MG-08).
- 19. Projects that are routed through the DAPCZ process are required to coordinate with the Office of Special Events (512-9741000 or TransportationSpecialEvents@austintexas.gov), in conjunction with the ROW Division of ATD. Visit City Stage for scheduled events for all of Austin.
- 20. Pursuant to City Code 9-2-3, ROW work must not make noise audible to an adjacent business or residence between 10:30pm and 7:00am or operate a machine that separates, gathers, grades, loads, or unloads sand, rock, or gravel within 600 feet of a residence, church, hospital, hotel, or motel between 7:00pm and 6:00am, except for installation of concrete authorized by a separate non-peak hour concrete pour permit issued under City Code section 9-2-21.