

## **Building Design Calculation** Worksheet

Building a Better and Safer Austin Together

Approved By:	Date:

DevelopmentATX.com | Phone: 311 or (512) 974-2000 outside Austin For submittal and fee information, see austintexas.gov/digitaldevelopment

The following worksheet must be completed for the following types of projects: commercial development of 10,000 square feet or more, commercial development of less than 10,000 square feet that contains any exterior trademarked design feature, any building currently zoned for industrial or warehouse use being converted to commercial, and/or VMU buildings with external trademarked design features (excluding signs). The worksheet must be completed by the applicant for each building in a project.

Download document before entering information.				
Project Name: Address:				
Feature Requested (as shown on plans)	Points Required	Design Option Provided (as shown on plans) See Subchapter E for details and definitions	Points Earned	
Required Base Point (1 pt)	1	Group A Options	•	
		☐ Star rating under the Austin Energy Green		
		Building Program. Each star of the rating		
Exterior Trademarked Design Feature located		qualifies for one point. No double credit for		
12 feet or less above finished grade and there is		Green Building points from Group B. Submit		
no prototypical roof or parapet design (3 pts)		GBP Conditional Approval & 1 set of GBP		
		Approved Plans with Building Plan application		
		(1-5 pts)		
☐ Exterior Trademarked Design Feature located		☐ Linear stores in building façade (1 pt each		
more than 12 feet above finished grade (5 pts) <sup>1</sup>		store)		
Features (1 pt each)		Façade articulation (1 pt)		
One-story building greater than 20 feet tall		Primary entrance design (1 pt)		
☐ 200+ foot façade w/out entrance every 75 feet		Roof design (1 pt)		
☐ Individual use larger than 100,000 sq. ft.		Use of limestone or non-trademark brick as		
		the primary building material (1 pt)		
☐ False fronts or shaped parapets		Increased use of glazing to conform with		
☐ Concrete block (excluding split-faced concrete		Section 3.2.2 on existing buildings (1 pt)  100% of glazing used on ground-floor facades		
block) used on more than 25% of publicly visible		facing streets or parking lots have a Visible		
facade		Transmittance (VT) of 0.6 or higher (1 pt)		
☐ EIFS used as a material on the ground floor		☐ Compliance with neighborhood design	<u> </u>	
below 10 feet		guidelines (1 pt)		
Pad building with drive-in or drive-through on a		gardomico (1 pty	·	
site with a Core Transit Corridor as the principal		Group B Options		
street		<b> </b>		
Features (2 pts each)		75% of the façade facing the principal street is store fronts with a minimum of 2 separate entrances (2 pts)		
☐ Pad-site building located in CBD or DMU district with a drive-in or drive-through		Sustainable roof (2 pts)		
Pad-site building located in CBD or DMU district				
that is separated from other buildings by surface		☐ Integrated solar power generation in building		
parking on two or more sides		design (2 pts)		
Concrete block (excluding split-faced concrete		Austin Energy Green Building Program rating		
block) used on more than 75% a publicly visible		of 2 Stars. Submit GBP Conditional Approval		
facade		with Building Plan application (2 pts)		
Total Points Required		Total Points Earned		
	Box A		Box B	
To determine compliance with the requirements of Subchapter E, Section 3.3 (Options to Improve Building Design), subtract the points in Box B form the points in Box A. If the result is less than or equal to 0, adequate design options have been provided.  Total Points Required: Total Points Earned: =				
<sup>1</sup> 2 points must be earned through the use of a design option in Group B if the feature is located more than 12 feet above finished grade.				
Applicant Signature: Date:				
· · · · · · · · · · · · · · · · · · ·				