

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

City of Austin Standard Details:

The use of these standard details is governed by the **Texas Engineering Practice Act** and the latest edition of the **Texas Manual Uniform of Traffic Control Devices (TMUTCD)**. The temporary traffic control (TTC) selected for each situation should be based on engineering judgment with consideration of issues such as type of highway, road user conditions, duration of operation, physical constraints, and the nearness of the work space to road users as per TMUTCD Section 6A.01 Paragraph 13. Any use of standard details must match existing field conditions. The following details is general guidance on what details could be allowed after the appropriate engineering judgement.

Sheet Number	Title	Can be applied to the following:	Notes
804S-1 Sheet 1	Arterial One Lane Closure	Level 3 and 4 streets	
804S-1 Sheet 2	One Way Arterial Two-Lane Closure	Level 3 and 4 streets	Double lane closures prohibited in DAPCZ from Monday through Friday per TCM Section 8.
804S-1 Sheet 3	Two Way Divided Arterial One Lane Closure	Level 3 and 4 streets	
804S-1 Sheet 4	Bypass walkway Sidewalk and Crosswalk Closures	All street levels	<ul style="list-style-type: none">• PROWAG R205 and TMUTCD Section 6D.01 Paragraph 9 prioritizes maintaining pedestrian access (diversion path) on the same side of the street compared to full closure of the pedestrian path and detour across the street• When existing pedestrian facilities are disrupted, closed or relocated in a temporary traffic control (TTC) zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Where pedestrians with visual disabilities normally use the closed sidewalk, a barrier that is detectable by a person with a visual disability traveling with the aid of a long cane shall be placed across the full width of the closed sidewalk (TMUTCD Section 6D.02)

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

804S-1 Sheet 5	Collector/Residential Lane Closures	REFER TO THE 804S-2 SERIES FOR FLAGGING. DO NOT USE THIS SHEET.	
804S-1 Sheet 6	Typical Traffic Control Plan for Shifting Traffic	Level 3 and 4 streets	
804S-1 Sheet 7	Typical Traffic Control Plan for Shifting Traffic	Level 3 and 4 streets	
804S-1 Sheet 8 and 9	GENERAL NOTES SHALL APPLY TO ALL SHEETS		
804S-1 Sheet 10	Bike Lane Closure and Bike Lane Closure with Adjacent Travel Lane	REFER TO THE 804S-1B SERIES FOR BIKE LANES. DO NOT USE THIS SHEET.	
804S-1 Sheet 11	Bike Lane Adjacent to Curb and Bike Lane Adjacent to Parking Lane	REFER TO THE 804S-1B SERIES FOR BIKE LANES. DO NOT USE THIS SHEET.	
804S-1 Sheet 12	Shared Bike Lane, Shared Bike Lane Parking Lane, Lane Channelizing into Bike Lane & Parking Lane	REFER TO THE 804S-1B SERIES FOR BIKE LANES. DO NOT USE THIS SHEET.	
804S-1 Sheet 13	Single Lane Closure on a Three Lane Roadway w/ Bike Lanes	REFER TO THE 804S-1B SERIES FOR BIKE LANES. DO NOT USE THIS SHEET.	

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

804S-1B Sheet 3	STANDARD NOTES SHALL APPLY TO Sheet 4 through Sheet 7		
804S-1B Sheet 4-Sheet 7	MERGING CYCLISTS STANDARD DETAILS	Bike Lane Closure <ul style="list-style-type: none"> • Level 1 streets • Level 2 streets where it is under 5,000 ADT 	Cyclist merging can only occur when ALL of the following field conditions are met: <ul style="list-style-type: none"> • 30 MPH or less (not 35 MPH or less as indicated on detail) • Under 5,000 ADT • NOT LOCATED ON AN ALL AGES AND ABILITY (AAA) NETWORK BIKE FACILITY AS IDENTIFIED BY THE LATEST EDITION OF THE AUSTIN STRATEGIC MOBILITY PLAN (ASMP) OR DOES NOT IMPACT SUCH A FACILITY FOR MORE THAN 14 DAYS (2 WEEKS)
804S-1B Sheet 3	STANDARD NOTES SHALL APPLY TO Sheet 9 through Sheet 14		
804S-1B Sheet 8,10,12	BICYCLISTS BYPASS STANDARD DETAIL (Long-Term Set up only)	REQUIRES ROW ENGINEERING REVIEW BEFORE IMPLEMENTING	Protected bike lanes can be used on ANY street levels
804S-1B Sheet 9,11,13,14	BICYCLISTS BYPASS STANDARD DETAIL (Daily Set up)	CAN BE USED ON ALL STREET LEVELS	Protected bike lanes can be used on ANY street levels

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

804S-4 Sheet 3	Large Excavation	All Street Levels	Must meet all positive protection and clear zone requirements as set in the TCM. Safety fence or barricades must comply with ADA/PROWAG compliance when channelizing pedestrians
804S-4 Sheet 4	Work Area Protection	All Street Levels	Must meet all positive protection, clear zone, and slope requirements (TxDOT).
804S-4 Sheet 5, 6, and 7	Steel Plating	Case 1 can be allowed on Level 1 Streets Case 2 can be allowed on Level 1, 2, 3, and 4 streets	
804S-4 Sheet 8 & 9	Material and Equipment Storage		Must meet all positive protection and clear zone requirements as set in the TCM. Safety fence or barricades must comply with ADA/PROWAG compliance when channelizing pedestrians.

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

TxDOT Standard Details

The use of these standard details is governed by the **Texas Engineering Practice Act** and the latest edition of the **Texas Manual Uniform of Traffic Control Devices (TMUTCD)**. The temporary traffic control (TTC) selected for each situation should be based on engineering judgment with consideration of issues such as type of highway, road user conditions, duration of operation, physical constraints, and the nearness of the work space to road users as per TMUTCD Section 6A.01 Paragraph 13. Any use of standard details must match existing field conditions. The following details is general guidance on what details could be allowed after the appropriate engineering judgement.

All TxDOT notes shall apply when using these standard details. Take note regarding the work duration in order to determine if the detail is allowed.

Sheet Number	Sheet Name	Can be applied to the following:	Notes
TCP(1-1)-18	Conventional Road Shoulder Work	All Street Levels	
TCP(1-2)-18	One-Lane Two-Way Traffic Control	TCP(1-2a) Control With Yield Signs (Less than 2000 ADT) <ul style="list-style-type: none"> Level 1 Street only TCP(1-2b) Control With flaggers <ul style="list-style-type: none"> Level 1 and 2 Streets only (minus Critical Arterials) 	<ul style="list-style-type: none"> Driveways create a problem that should be monitored by flaggers (TMUTCD TA-10, Note #12)
TCP(1-3)-18	Traffic Shifts on Two Lane Roads	Level 1 and 2 Streets	
TCP(1-4)-18	Lane Closures on Multilane Conventional Roads	Level 3 and 4 Streets	
TCP(1-5)-18	Lane Closures for Divided Highways	Level 2, 3, and 4 Streets	
TCP(1-6)-18	Automated Flagger Assistance Devices (AFAD)	Level 1 and 2 Streets (minus Critical Arterials)	
TCP(2-1)-18	Conventional Road Shoulder Work	All Street Levels	

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

TCP(2-2)-23	One-Lane Two-Way Traffic Control	TCP(1-2a) Control With Yield Signs (Less than 2000 ADT) <ul style="list-style-type: none"> Level 1 Street only TCP(1-2b) Control With flaggers Level 1 and 2 Streets only (minus Critical Arterials)	<ul style="list-style-type: none"> Driveways create a problem that should be monitored by flaggers (TMUTCD TA-10, Note #12)
TCP(2-3)-23	Traffic Shifts on Two-Lane Roads	Level 1 and 2 Streets	**Note that long-term pavement markings are required by TxDOT (TCP2-3b)
TCP(2-4)-18	Lane Closures on Multilane Conventional Roads	Level 3 and 4 Streets	
TCP(2-5)-18	Long Term Lane Closures Multilane Conventional RDS (Roads)	Level 3 and 4 Streets	
TCP(2-6)-18	Lane Closures on Divided Highways	Level 3 and 4 Streets	
TCP(2-7)-23	Diversions and Narrow Bridges	REQUIRES ROW ENGINEERING REVIEW BEFORE IMPLEMENTING	
TCP(2-8)-23	Long Term One-Lane Two Way Control	REQUIRES ROW ENGINEERING REVIEW BEFORE IMPLEMENTING	
TCP(3-1)-13	Mobile Operations Undivided Highways	All Street Levels	
TCP(3-2)-13	Mobile Operations Divided Highways	Level 3 and 4 Streets	
TCP(3-3)-14	Mobile Operations Raised Pavement marker	All Street Levels	
TCP(3-4)-14	Mobile Operations for Isolated Work Areas Undivided Highways	All Street Levels	
TCP(3-5)-18	Mobile Operations Herbicide Truck Operations	All Street Levels	
TCP(5-1)-18	Shoulder Work for Freeways/Expressways	All Street Levels	

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

TCP(6-1)-12	Freeway Lane Closures	Level 3 and 4 Streets	
TCP(6-2)-12	Work Area Near Ramp	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(6-3)-13	Work Area Beyond Ramp	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(6-4)-12	Work Area at Exit Ramp	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(6-5)-12	Work Area Beyond Exit Ramp	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(6-6)-12	Freeway Closure	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(6-7)-12	Short Duration Freeway Closure Sequence	REQUIRES ROW ENGINEERING REVIEW BEFORE IMPLEMENTING (DETAIL MENTIONS THAT THIS PLAN IS FOR TRAFFIC VOLUMES WHICH ARE <u>LESS THAN 1000</u> PASSANGER CARS PER HOUR PER LANE (PCPHPL) [NOT ADT/AADT]).	
TCP(6-8)-14	Work in Exit Gore for ADT Less than 10,000 ADT	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(6-9)-14	Work in Exit Gore for ADT Greater than 10,000 ADT	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(7-1)-12	Traffic Control Details for Surfacing Operations	Level 1 and 2 Streets	<p>This can ONLY be used when bike lanes are NOT present.</p> <p>This only contains the signs and temporary pavement markings</p>
TCP(S-1)-08A	Traffic Control for Surveying Operations	Level 1 and 2 Streets	
TCP(S-2)-08A	Traffic Control for Surveying Operations	Level 1 and 2 Streets	<ul style="list-style-type: none"> • Driveways create a problem that should be monitored by flaggers (TMUTCD TA-10, Note #12)
TCP(S-2c)-10	Traffic Control for Surveying Operations	Level 1 and 2 Streets	<ul style="list-style-type: none"> • Driveways create a problem that should be monitored by flaggers (TMUTCD TA-10, Note #12)

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

TCP(S-3)-08 TCP(S-4)-08A TCP(S-5)-08	Traffic Control for Surveying Operations	Level 3 and 4 Streets	
TCP(SC-1)-22	Seal Coat Operations One-Lane Two-Way	Level 1 and 2 Streets	<ul style="list-style-type: none"> • Driveways create a problem that should be monitored by flaggers (TMUTCD TA-10, Note #12)
TCP(SC-2)-22	Seal Coat Operations Multilane Roads (Undivided)	Level 3 and 4 Streets	
TCP(SC-3)-22	Seal Coat Operations Multilane Roads (Center Turn Lane)	Level 3 and 4 Streets	
TCP(SC-4)-22	Seal Coat Operations Near Intersections	Level 1 and 2 Streets	
TCP(SC-5)-22	Seal Coat Operations Divided Highways	Level 3 and 4 Streets	
TCP(SC-6)-22	Seal Coat Operations – Divided Highway	This is typically for Level 5 (which will be deferred to TxDOT)	
TCP(SC-7)-22	Temporary Pavement Markings for Seal Coat Operations	All Street Levels	
TCP(SC-8)-22	Traffic Control Details for Seal Coat Operations	Level 1 and 2 Streets	
-	Traffic Control Plan Emergency Road Closure (Ice Conditions)	This is typically for Level 5 (which will be deferred to TxDOT)	
-	Treatment for Various Edge Conditions (Positive Protection)	All Street levels	Ensure that all requirements also meet the Transportation Criteria Manual (TCM)
BC(1)-21	General Notes and Requirements	All Street Levels	This sheet can be used to accompany the latest City of Austin Right-of-Way (ROW) standard notes

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

BC(2)-21 BC(3)-21	Work Zone Speed Limits	REQUIRES ROW ENGINEERING REVIEW BEFORE IMPLEMENTING ANY REGULATORY SPEED LIMITS. PLEASE CONTACT DARREN UJANO AT DARREN.UJANO@AUSTINTEXAS.GOV FOR REVIEW	
BC(4)-21 BC(5)-21	Temporary Sign Notes Typical Sign Support	All Street Levels	
BC(6)-21	Portable Changeable Message Sign (PCMS)	All Street Levels	Only need to use this sheet when deploying PCMS/DMS
BC(7)-21 BC(8)-21 BC(9)-21 BC(10)-21 BC(11)-21 BC(12)-21	Arrow Panel, Reflectors, Warning Lights & Attenuator Channelizing Devices Pavement Markings Pavement Marking Patterns	All Street levels	
WZ(TD)-17	Traffic Control Plan Typical Details	Barrie Delineation with Modular Glare Screens <ul style="list-style-type: none"> All Street Levels Vertical Panels & Opposing Traffic Lane Dividers (OTLD) Separating Two-Way Traffic on Normally Divided Highways <ul style="list-style-type: none"> Level 1 and 2 Streets 	
WZ(STPM)-23	Work Zone Short Term Pavement Markings	All Street Levels	
WZ(UL)-13	Signing for Uneven Lanes	All Street Levels	
WZ(RCD)-13	Work Zone Road Closure Details	Level 1 and 2 Streets (minus critical arterials and streets with bike lanes)	Level 3 and 4 will require ROW engineering review due to the high-volume of vehicles being detoured (above 10k+). Bike lane closures will require a detour.
WZ(BTS-1)-13	Traffic Signal Work Typical Details	All Street Levels	
WZ(BRK)-13	Work Zone Give Us a Brake	All Street Levels	
WZ(RS)	Temporary Rumble Strips	All Street Levels	Take note of the ADT under Table 1 and Table 2 regarding number

Guidelines for Functional Classification to Austin Strategic Mobility Plan (ASMP)

			of rumble strips, distance between strips, and flagger distance
TLRS(1)-17 TLRS(2)-17 TLRS(3)-17 TLRS(4)-17	Temporary Large Roadside Signs Mounting Details	All Street Levels	Note that embedding signs into the ground will require an EX permit
TS-CD-22	Temporary Large Sign Covering Details	This is typically for Level 5 (which will be deferred to TxDOT)	
WZ-ITS(1)-19 WZ-ITS(2)-19 WZ-ITS(3)-19	Temporary Queue Detection System Type 1	All Street Levels	
WZ-ITS(3)-19	Temporary Queue Detection System Type 2	All Street Levels	