

CITY OF AUSTIN STANDARD PRODUCTS LIST

for

POLYETHYLENE ELECTROFUSION FITTINGS (4-INCH TO 16-INCH DIAMETER)

USING DEPARTMENT: Austin Water **PREPARED BY:** Jeff A. Kyle, P.E. **ISSUED:** 01/01/22

REVISED BY: REVISED:

DESCRIPTION: Electrofusion fittings, polyethylene (PE) for wastewater force mains only, 4 inch to 16 inch

nominal diameter meeting the following requirements:

1. Compliance with AWWA C906

2. Compliance with ASTM F1055, with additional requirement that markings include size followed by DIPS

- 3. Materials Designation Code of PE4710 (Cell Class: 445574C)
- 4. Ductile Iron Pipe Size (DIPS) OD compatibility
- 5. Minimum Pressure Rating of 200 psi

LISTING DATE	MANUFACTURER	PRODUCT IDENTIFICATION/COMMENT	APPROVAL
01/01/22	GEORG FISCHER CENTRAL PLASTICS 39605 W. Independence Avenue Shawnee, OK 74804	Flex Restraints	J. Kyle
01/01/22	INTEGRITY FUSION PRODUCTS, INC. 270 Parkade Court Peachtree City, GA 30269	Flex Restraints	J. Kyle
01/01/22	STRONGBRIDGE INTERNATIONAL, LLC 154 Industrial Loop South Orange Park, FL 32073	Flex Restraints	J. Kyle

NOTES:

- 1. Fitting material must comply with requirements of the description above and be rated above design pressure.
- 2. Sizes for wastewater force mains shall be determined based on specific project requirements.
- 3. These fittings shall only be used with PE pipe listed on SPL WW-706 and are not to be used for gravity flow wastewater systems.
- 4. Each fusion technician must be pre-qualified and possess a current certification issued by an independent, industry-recognized certification organization to make electrofusion joints.

LATEST REVISIONS:

1. New SPL